



dLAN 200 AVdesk Starter Kit



Technical data

Standards	- Ethernet specifications IEEE 802.3, IEEE 802.3x, IEEE 802.3u, Auto MDI / X - HomePlug AV
Protocols	TDMA, CSMA/CA
Transmission speed	200 Mbps
Transmission method	asynchronous
Modulation	OFDM - 1155 carriers, 1024/256/64-QAM, QPSK, BPSK
Data path	Ethernet <-> power supply grid
Range	200m over household power supply grid
Security	128-bit AES encryption over household power supply grid
LEDs	- Power - dLAN (Link/Act) - Ethernet (100/Act) - Ethernet (10/Act) - Ethernet Collision
dLAN port	Euro mains plug
Device port	Ethernet RJ45
Weight	230 g
Dimensions	153 x 105 x 35 mm (height x width x depth)
Power consumption	5.5 W (max.)
Power supply	AC 100-240V 50/60Hz
Temperature	Storage: -25°C – 70°C Operation: 0°C – 40°C
Ambient conditions	10–90% humidity (non-condensing)
System requirements	Ethernet port
Operating systems	Windows® 98, Windows® ME, Windows® 2000, Windows® XP, Linux®, Mac OS® X and all operating systems with TCP/IP support
Certifications	CE-compliant in accordance with the technical requirements of all EU countries and Switzerland: EN 55022 EN 50412 EN 60950



dLAN 200 AV_{desk} Starter Kit



Sales information

Article number	01185 (DE/AT/CH/BE/IT), 01184 (NL,ESP), 01186 (UK), 01187 (FR)
EAN-Code	4250059611856 (DE/AT/CH/BE/IT), 4250059611849 (NL,ESP), 4250059611863 (UK), 4250059611870 (FR)
Warranty	3 years
Service & Support	Telephone and e-mail support. Please see the included support flyer or the devolo website for telephone numbers and e-mail addresses.
Design	Plastic desktop housing
Weight	1170 g
Package dimensions	188 x 302 x 115 mm (height x width x depth)
Accessories	2 Ethernet cables RJ45-RJ45 (Cat 5) 2 power cables - Documentation: printed installation guide - CD-ROM: PDF manual, configuration software for Windows®, Linux®, Mac OS® X, additional software: devolo Informer, devolo Easyshare, devolo Easyclean